

Silicon PNP Power Transistors

2SB944

DESCRIPTION

- With TO-220Fa package
- Large collector current I_C
- Low collector saturation voltage
- Complement to type 2SD1269

APPLICATIONS

- For power switching applications

PINNING

PIN	DESCRIPTION
1	Base
2	Collector
3	Emitter




Fig.1 simplified outline (TO-220Fa) and symbol

Absolute maximum ratings($T_a=25$)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	Open emitter	-130	V
V_{CEO}	Collector-emitter voltage	Open base	-80	V
V_{EBO}	Emitter-base voltage	Open collector	-7	V
I_C	Collector current		-4	A
I_{CM}	Collector current-peak		-8	A
P_C	Collector power dissipation	$T_a=25$	2	W
		$T_C=25$	35	
T_j	Junction temperature		150	
T_{stg}	Storage temperature		-55~150	

Silicon PNP Power Transistors

2SB944

CHARACTERISTICS

T_j=25 unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-emitter breakdown voltage	I _C =-10mA, I _B =0	-80			V
V _{CEsat}	Collector-emitter saturation voltage	I _C =-3A, I _B =-0.15A			-0.5	V
V _{BEsat}	Base-emitter saturation voltage	I _C =-3A, I _B =-0.15A			-1.5	V
I _{EBO}	Emitter cut-off current	V _{EB} =-5V; I _C =0			-50	μA
I _{CBO}	Collector cut-off current	V _{CB} =-100V; I _E =0			-10	μA
h _{FE-1}	DC current gain	I _C =-0.1A; V _{CE} =-2V	45			
h _{FE-2}	DC current gain	I _C =-1A; V _{CE} =-2V	90		260	
f _T	Transition frequency	I _C =-0.5A; V _{CE} =-10V; f=10MHz		30		MHz

Switching times

t _{on}	Turn-on time	I _C =-1A; I _{B1} =-I _{B2} =-0.1A		0.15		μs
t _{stg}	Storage time			0.8		μs
t _f	Fall time			0.15		μs

◆ h_{FE-2} Classifications

Q	P
90-180	130-260

Silicon PNP Power Transistors

2SB944

PACKAGE OUTLINE




Fig.2 Outline dimensions (unindicated tolerance: ± 0.15 mm)