

Silicon NPN Power Transistors

2SC4160

DESCRIPTION

- With TO-220F package
- High breakdown voltage.
- High reliability.
- Fast switching speed
- Wide ASO (Safe Operating Area)

APPLICATIONS

- 400V/4A Switching Regulator Applications

PINNING

PIN	DESCRIPTION
1	Base
2	Collector
3	Emitter




Fig.1 simplified outline (TO-220F) and symbol

Absolute maximum ratings (Ta=25)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	Open emitter	500	V
V_{CEO}	Collector-emitter voltage	Open base	400	V
V_{EBO}	Emitter-base voltage	Open collector	7	V
I_C	Collector current		4	A
I_{CM}	Collector current-peak		8	A
I_B	Base current		1.5	A
P_C	Collector dissipation	$T_C=25$	25	W
			2	
T_j	Junction temperature		150	
T_{stg}	Storage temperature		-55~150	

Silicon NPN Power Transistors

2SC4160

CHARACTERISTICS

T_j=25 unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CEO}	Collector-emitter breakdown voltage	I _C =5mA ; R _{BE} =	400			V
V _{CBO}	Collector-base breakdown voltage	I _C =1mA ; I _E =0	500			V
V _{EBO}	Emitter-base breakdown voltage	I _E =1mA ; I _C =0	7			V
V _{CEsat}	Collector-emitter saturation voltage	I _C =2A ; I _B =0.4A			0.8	V
V _{BEsat}	Base-emitter saturation voltage	I _C =2A ; I _B =0.4A			1.5	V
I _{CBO}	Collector cut-off current	V _{CB} =400V ; I _E =0			10	μA
I _{EBO}	Emitter cut-off current	V _{EB} =5V ; I _C =0			10	μA
h _{FE-1}	DC current gain	I _C =0.4A ; V _{CE} =5V	15		50	
h _{FE-2}	DC current gain	I _C =2A ; V _{CE} =5V	10			
h _{FE-3}	DC current gain	I _C =10mA ; V _{CE} =5V	10			
C _{OB}	Output capacitance	I _E =0 ; V _{CB} =10V ; f=1MHz		50		pF
f _T	Transition frequency	I _C =0.4A ; V _{CE} =10V		20		MHz

Switching times

t _{on}	Turn-on time	I _C =3A ; I _{B1} =0.6A I _{B2} =-1.2A V _{CC} =200V , R _L =66.6			0.5	μs
t _s	Storage time				2.5	μs
t _f	Fall time				0.3	μs

◆ h_{FE-1} Classifications

L	M	N
15-30	20-40	30-50

Silicon NPN Power Transistors

2SC4160

PACKAGE OUTLINE




Fig.2 Outline dimensions